



Lighting Like No Other

LED FLOOD LIGHT TP-02 SERIES

Model : ECO-FL10W-TP-02



Features

- Soft light with high light effect.
- Low power consumption, long lifespan
- Good stability, High reliability
- No harmful metal mercury & environmental protection
- Weather Proof (IP65)
- Available in various color temperature and voltage
- 80% reduction in energy consumption
- Easy to install & adjust

Photoelectric Specification

Power Consumption	10 W
Input Voltage	100 – 265 VAC
Input Frequency	50/60Hz
Power Factor (PF)	> 0.90
Luminaire	900 lm
Beam Angle (deg)	120°
Driver	Isolated

Light Source Specification

LED Chip	SMD 5730
Color Accuracy	CRI > 70
Color Temperature	WW(3000 –3500K) NW(4000-4500K) CW (5000-6500K)

Environment Specification

Operation Temperature Range	-20-50°C
Preservation Temperature Range	-40-60°C
Operation Humidity Range	95%Rh or Below(@-20°C-50°C)

Certification Standard





Lighting Like No Other

LED FLOOD LIGHT TP-02 SERIES

Model : ECO-FL20W-TP-02



Features

- Soft light with high light effect.
- Low power consumption, long lifespan
- Good stability, High reliability
- No harmful metal mercury & environmental protection
- Weather Proof (IP65)
- Available in various color temperature and voltage
- 80% reduction in energy consumption
- Easy to install & adjust

Photoelectric Specification

Power Consumption	20 W
Input Voltage	100 – 265 VAC
Input Frequency	50/60Hz
Power Factor (PF)	> 0.90
Luminaire	1900 lm
Beam Angle (deg)	120°
Driver	Isolated

Light Source Specification

LED Chip	SMD 5730
Color Accuracy	CRI > 70
Color Temperature	WW(3000 –3500K) NW(4000-4500K) CW (5000-6500K)

Environment Specification

Operation Temperature Range	-20-50°C
Preservation Temperature Range	-40-60°C
Operation Humidity Range	95%Rh or Below(@-20°C-50°C)

Dimension

Dimension (L*W*H)mm	162.1mm*135.55mm*51.5mm
Weight (KG)	0.64kg

Certification Standard





Lighting Like No Other

LED FLOOD LIGHT TP-02 SERIES

Model : ECO-FL30W-TP-02



Features

- Soft light with high light effect.
- Low power consumption, long lifespan
- Good stability, High reliability
- No harmful metal mercury & environmental protection
- Weather Proof (IP65)
- Available in various color temperature and voltage
- 80% reduction in energy consumption
- Easy to install & adjust



Photoelectric Specification

Power Consumption	30 W
Input Voltage	100 – 265 VAC
Input Frequency	50/60Hz
Power Factor (PF)	> 0.90
Luminaire	3000 lm
Beam Angle (deg)	120°
Driver	Isolated

Light Source Specification

LED Chip	SMD 5730
Color Accuracy	CRI > 70
Color Temperature	WW(3000 –3500K) NW(4000-4500K) CW (5000-6500K)

Environment Specification

Operation Temperature Range	-20-50°C
Preservation Temperature Range	-40-60°C
Operation Humidity Range	95%Rh or Below(@-20°C-50°C)

Dimension

Dimension (L*W*H)mm	212.1mm*169.05mm*52.5mm
Weight (KG)	1.15kg

Certification Standard





Lighting Like No Other

LED FLOOD LIGHT TP-02 SERIES

Model : ECO-FL50W-TP-02



Features

- Soft light with high light effect.
- Low power consumption, long lifespan
- Good stability, High reliability
- No harmful metal mercury & environmental protection
- Weather Proof (IP65)
- Available in various color temperature and voltage
- 80% reduction in energy consumption
- Easy to install & adjust

Photoelectric Specification

Power Consumption	50 W
Input Voltage	100 – 265 VAC
Input Frequency	50/60Hz
Power Factor (PF)	> 0.90
Luminaire	5000 lm
Beam Angle (deg)	120°
Driver	Isolated

Light Source Specification

LED Chip	SMD 5730
Color Accuracy	CRI > 70
Color Temperature	WW(3000 –3500K) NW(4000-4500K) CW (5000-6500K)

Environment Specification

Operation Temperature Range	-20-50°C
Preservation Temperature Range	-40-60°C
Operation Humidity Range	95%Rh or Below(@-20°C-50°C)

Dimension

Dimension (L*W*H)mm	277.0mm*277.0mm*61.5mm
Weight (KG)	1.96kg

Certification Standard

